


Automatic On-Line Cable insulation Monitoring system

AOLCM

Product appearance



Measuring panel




Grounding box for GTR neutral point



Grounding box for EVT neutral point

Supply record



Measuring panel



Central monitoring station

Please inform us of the following data for the estimation of the system.

•Single line connection diagram

Voltage, grounding method, number of buses, GTR / EVT capacity and number

•Feeder list

Number of lines, number of cores[single core (including triplex), 3-cores], conductor size

Sumitomo Electric Industries, Ltd.

Energy Solution Sales Div.

1-3-13, Akasaka Minato-Ku, Tokyo-to 107-8468, Japan

TEL:+813-6406-2798 FAX:+813-6406-4088

Power Cables engineering & Construction Div.

4-7-7, Higashikojiya Ota-Ku, Tokyo-to 144-0033, Japan

TEL:+813-6423-8090 FAX:+813-3742-1302

5-5-23, Torishima Konohana-Ku, Osaka-shi 554-0051, Japan

TEL:+816-6462-5052 FAX:+816-6462-5054

Technical supervisor Email : olcm@info.sei.co.jp

Fully automatic monitoring of deterioration of XLPE insulated cables 3.3 to 11kV
Powerful support for preventive cable maintenance!

Powerful support for preventive maintenance

- AOLCM is the latest tool for preventive maintenance from cable insulation breakdown and allows the uninterrupted continuous operation of factories and buildings.
- AOLCM can improve the precision of cable insulation deterioration and the judgment of renewal of cables.
- Also, you can monitor from a branch station connected to the AOLCM central monitoring station via internal network.

Fully automatical measurement of the insulation resistance of high-voltage cables and bus

[Object of measurement]

- XLPE insulated cables 3.3~11kV, single-core, triplex, 3-cores

[Measuring items]

- Insulation resistance of cable main insulation (Ri)
- Insulation resistance of cable sheath (Rs)
- Conducting resistance of shielding layer (RT) * except 3-cores
- Insulation resistance of bus (RB)

AOLCM automatically processes the measured values and raises an alarm once abnormality happens. Preventive maintenance according to the situation is possible.

[Statistic display]

- List of measured values of all feeders for each measurement date
- Measured value list for each feeder •Monthly / Annual report chart
- Time series chart for each feeder for measurement item
- Estimated remaining lifetime curve of cable main insulation resistance for insulation failure.

Measurement principle

•Ri measurement

Measurement voltage (DC50V) shall be applied between cable conductor and shielding layer through primary neutral point of GTR (or EVT) and busbar. DC leakage current of cable insulation shall be transported to measuring panel and measured to insulation resistance.

•Rb measurement

DC leakage current of bus line by applying DC50V shall be measured to insulation resistance.

•Rs measurement

Measurement voltage (DC5V) shall be applied between cable shielding layer and the earth. DC leakage current of cable sheath shall be transported to measuring panel and measured to insulation resistance.

•RT measurement

For RT measurement, each cable shielding layer shall be connected at the point of load side of a feeder line. By the connection, loop line of shielding is formed. Measurement voltage (DC5V) shall be applied between one phase and the connection of another two phases. Measurement shall be done for 3 phases. Resistance of each shielding layer is calculated from the measured currents.


Measurable range (example)

Item	Measurable range	
Main insulation(Ri)	10MΩ~10000MΩ	
Cable sheath(Rs)	0kΩ~10MΩ	
Shielding layer(RT)	0Ω~1kΩ	
Bus(RB)	Ungrounded	2kΩ~20MΩ
	Resistance grounded	4kΩ~5MΩ


Judgment criteria (recommended value)

Item	Measured value	Judgment	Action
Ri : Main insulation [6.6kV cable]	$Ri \geq 3000M\Omega$	Good	Not necessary
	$3000M\Omega > Ri \geq 300M\Omega$	Slight deterioration	Monitoring carefully
	$300M\Omega > Ri \geq 30M\Omega$	Medium deterioration	Renewal shall be considered and planned.
	$30M\Omega > Ri$	Serious deterioration	Cable shall be renewed immediately.(Cable will go to breakdown soon.)
Rs: Cable sheath	$Rs \geq 1M\Omega$	Good	Not necessary
	$1M\Omega > Rs$	Not good	Localization and repair work is recommended.
RT: Shielding layer	$100\Omega > RT$	Good	Not necessary
	$RT \geq 100\Omega$	Not good	Localization and repair work is recommended.
RB: Bus	Judgment shall be done by considering the condition of bus because no criteria is available.		

System construction and measurement circuit (example of neutral grounded system)




Example of measured values list




- display with colored letter
- Ri : 3 criterion steps according to the degree of deterioration
- Rs : red letter for the value less than 1MΩ
- RT : red letter for the value more than 100Ω

Example of time series chart (6.6kV)



- You can understand the degree of cable deterioration at a look of the chart.
- You can judge the cable renewal with high precision in advance.



- You can estimate remaining lifetime curve based on measured values.